

## Technical data sheet

### Safety relay

Part no.: 547953

MSI-SR5B-02

#### Contents

- Technical data
- Electrical connection
- Operation and display



Figure can vary



## Technical data

### Basic data

Series	MSI-SR5B
--------	----------

### Functions

Functions	Automatic start/restart
	Contactormonitoring (EDM)
	Cross circuit monitoring
	Double sensor monitoring
	Start/restart interlock (RES), selectable
Restart	Automatic
	Manual

### Characteristic parameters

SIL	3, IEC 61508
SILCL	3, IEC/EN 62061
Performance Level (PL)	e, EN ISO 13849-1
MTTF <sub>d</sub>	73 years, EN ISO 13849-1
PFH <sub>D</sub>	1E-08 per hour
PFH <sub>D</sub> , nop = 4800	0.00000001 per hour
PFH <sub>D</sub> , nop = 28800	0.00000002 per hour
PFH <sub>D</sub> , nop = 86400	0.00000005 per hour
Mission time T <sub>M</sub>	20 years, EN ISO 13849-1
Category	4, EN ISO 13849
STOP category	0, IEC/EN 60204-1
B10 <sub>d</sub> at AC1 (ohmic load)	400,000 number of cycles
B10 <sub>d</sub> at DC13 (inductive load)	4,000,000 number of cycles

### Electrical data

Protective circuit	Fuse on switching output, upstream
Continuous current per current path, max.	2 A
Input current, max.	150 mA
External safeguarding for supply circuit	200 mA delay-action
External contact fuse protection per current path	5 A quick-action, or 3.15 A delay-action
Permissible input line resistance, max.	30 Ω

### Performance data

Supply voltage U <sub>B</sub>	24 V, DC, -20 ... 20 %
Current consumption, additional note	Without external load

### Outputs

Number of safety-related switching outputs (OSSDs)	2 Piece(s)
--	------------

### Safety-related switching outputs

Type	Safety-related switching output OSSD
Voltage type	DC

### Safety-related switching output 1

Switching element	Relay, NO
-------------------	-----------

### Safety-related switching output 2

Switching element	Relay, NO
-------------------	-----------

### Time behavior

Pickup delay, automatic start	350 ms
Pickup delay, manual start	50 ms
Regression delay	10 ms
Test pulse acceptance, max.	1 ms
Time window between 2 channels of a sensor, max.	60 ms

### Connection

Number of connections	1 Piece(s)
Connectible safety sensors (AOPDs)	Up to 2 AOPDs type 4, type 3 or type 2 self-testing
Connectible electro-mechanical safety devices	E-Stop command devices, 1 and 2-channel Safety switches

### Connection 1

Function	Connection to device
Type of connection	Terminal
Type of terminal	Spring-cage terminal
No. of pins	16 -pin

### Cable properties

Connection cross sections	0.2 to 1.5 mm <sup>2</sup>
---------------------------	----------------------------

### Mechanical data

Dimension (W x H x L)	22.5 mm x 111 mm x 114.1 mm
Housing material	Plastic
Plastic housing	PA 66
Net weight	170 g
Housing color	Gray
Type of fastening	Snap-on mounting
Mechanical life time	10,000,000 actuation cycles

### Operation and display

Type of display	LED
Number of LEDs	4 Piece(s)

### Environmental data

Ambient temperature, operation	0 ... 55 °C
Ambient temperature, storage	-25 ... 70 °C
Relative humidity (non-condensing)	0 ... 95 %

### Certifications

Degree of protection	IP 20 (terminals)
	IP 40 (housing)
Protection class	II
Certifications	c UL US
	TÜV Süd
US patents	US 6,418,546 B

## Technical data

Customs tariff number	85371098
ECLASS 5.1.4	27371800
ECLASS 8.0	27371819
ECLASS 9.0	27371819
ECLASS 10.0	27371819
ECLASS 11.0	27371819
ECLASS 12.0	27371819
ECLASS 13.0	27371819
ETIM 5.0	EC001449
ETIM 6.0	EC001449
ETIM 7.0	EC001449
ETIM 8.0	EC001449

## Electrical connection

### Connection 1

Function	Connection to device
Type of connection	Terminal
Type of terminal	Spring-cage terminal
No. of pins	16 -pin

### Terminal

### Assignment

5	+24 V
6	0 V
7	Sensor input 1 channel 2, 24V
8	Sensor input 2 channel 2, 24V
13	Sensor input 1 channel 2, 0V
14	Sensor supply, contacts 24V OUT
15	Sensor input 2 channel 2, 0V
16	Restart input
21	Sensor input 1 channel 1, 24V
22	Sensor supply contacts 0V OUT
23	Sensor input 2 channel 1, 24V
24	Restart automatic output
29	Relay contact 1 IN
30	Relay contact 1 OUT
31	Relay contact 2 IN
32	Relay contact 2 OUT

## Operation and display

LED	Display	Meaning
1	Green, continuous light	Supply voltage on
2	Green, continuous light	Channel 1
3	Green, continuous light	Channel 2
4	Orange, continuous light	Start/restart interlock locked