



BDF200-SD-NH-LTBU-LMGN-LMRD

- integrated SD interface for use in SD interface systems
- Pos 1: E-STOP
- Pos 2: BLUE illuminated pushbutton
- Pos 3: GREEN illuminated pushbutton
- Pos 4: RED signal light
- slender shock-proof thermoplastic enclosure
- to be installed at an ergonomic favourable position
- to be fitted to commercial-off-the-shelf aluminium profiles
- E-STOP with electronic OSSDs

Data

Ordering data

| | |
|-------------------------------|-----------------------------|
| Product type description | BDF200-SD-NH-LTBU-LMGN-LMRD |
| Article number (order number) | 103033342 |
| EAN (European Article Number) | 4030661531472 |
| eCl@ss number, version 12.0 | 27-37-12-16 |
| eCl@ss number, version 11.0 | 27-37-12-16 |
| eCl@ss number, version 9.0 | 27-37-12-16 |
| ETIM number, version 7.0 | EC000225 |
| ETIM number, version 6.0 | EC000225 |
| Note (Ordering data) | Notice: see ordering code |

Approvals - Standards

| | |
|--------------|--------------|
| Certificates | TÜV cULus |
|--------------|--------------|

General data

| | |
|----------------------------|----------------------------------------------------------------------------------------|
| Standards | EN ISO 13849-1 EN ISO 13850 EN IEC 60947-5-1 EN IEC 60947-5-5 EN IEC 61508 |
| Climatic stress | DIN EN 60068 |
| Housing material | Plastic, glass-fibre reinforced thermoplastic, self-extinguishing |
| Reaction time, maximum | 50 ms |
| Duration of risk, maximum | 100 ms |
| Positions used, position 1 | Emergency stop pushbutton |
| Positions used, position 2 | Illuminated pushbutton, blue |
| Positions used, position 3 | Indicator light, green |
| Positions used, position 4 | Indicator light, red |
| Gross weight | 280 g |

General data - Features

| | |
|-------------------------------------|-----|
| Serial diagnostics | Yes |
| Field box interface | 0 |
| Indicator lamp | No |
| Safety functions | Yes |
| Number of fail-safe digital outputs | 2 |

Safety classification

| | |
|------------------------------------------------------------|----------------------------------------|
| Standards | EN ISO 13849-1 EN IEC 61508 |
| Performance Level, up to | e |
| Category | 4 |
| PFH value | 2.89×10^{-10} /h |
| Note (PFH-value) | up to max. 5,000 switching cycles/year |
| Safety Integrity Level (SIL), suitable for applications in | 3 |
| Mission time | 20 Year(s) |

Mechanical data

| | |
|----------------------------------------|-------------------------|
| Mechanical life, Emergency-Stop button | 100,000 Operations |
| Mechanical life, Command devices | 1,000,000 Operations |
| Mounting | interior mounting holes |
| Type of the fixing screws | 2x M5 |

Mechanical data - Connection technique

| | |
|-----------------------|-------------------------------------|
| Terminal (mechanical) | Connector plug M12, 8-pole, A-coded |
|-----------------------|-------------------------------------|

Mechanical data - Dimensions

| | |
|-------------------------|-----------------------------------------------------------|
| Width | 40 mm |
| Height | 69 mm |
| Depth | 220 mm |
| Length x Width x Height | Depth: 233.5 - 252.5 mm (without and with indicator lamp) |

Ambient conditions

| | |
|------------------------------------------------------------|----------------------------------------|
| Degree of protection | IP65 |
| Ambient temperature | -25 ... +65 °C |
| Storage and transport temperature | -25 ... +85 °C |
| Resistance to vibrations | 10 ... 150 Hz, amplitude 0.35 mm / 5 g |
| Resistance to shock | 30 g / 11 ms |
| Protection class | III |
| Permissible installation altitude above sea level, maximum | 2,000 m |

Ambient conditions - Insulation values

| | |
|-------------------------------------------|--------|
| Rated insulation voltage U_i | 32 VDC |
| Rated impulse withstand voltage U_{imp} | 0.8 kV |

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical data

| | |
|----------------------------------------|-----------------------------------------------------|
| Operating voltage | 24 VDC -15 % / +10 % (stabilised PELV power supply) |
| No-load supply current I_0 , typical | 35 mA |
| Rated operating voltage | 24 VDC |
| Operating current | 600 mA |
| Required rated short-circuit current | 100 A |
| Time to readiness, maximum | 2,000 ms |
| Switching frequency, maximum | 1 Hz |

Electrical data - Safety digital inputs

| | |
|-----------------------------------|--------------------------------------------|
| Designation, Safety inputs | X1 and X2 |
| Switching thresholds | -3 V ... 5 V (Low) 15 V ... 30 V (High) |
| Current consumption at 24 V | 5 mA |
| Test pulse duration, maximum | 1 ms |
| Test pulse interval, minimum | 100 ms |
| Classification ZVEI CB24I, Sink | C1 |
| Classification ZVEI CB24I, Source | C1 C2 C3 |

Electrical data - Safety digital outputs

| | |
|-------------------------------------|-----------------------------|
| Designation, Safety outputs | Y1 and Y2 |
| Design of control elements | short-circuit proof, p-type |
| Voltage drop U_d , maximum | 1 V |
| Leakage current I_r , maximum | 0.5 mA |
| Voltage, Utilisation category DC-12 | 24 VDC |
| Current, Utilisation category DC-12 | 0.25 A |
| Voltage, Utilisation category DC-13 | 24 VDC |

| | |
|-------------------------------------|---------|
| Current, Utilisation category DC-13 | 0.25 A |
| Test pulse interval, typical | 1000 ms |
| Test pulse duration, maximum | 1 ms |
| Classification ZVEI CB24I, Source | C1 |
| Classification ZVEI CB24I, Sink | C1 |

Electrical data - Serial diagnostic SD

| | |
|-----------------------------------|-----------------------------|
| Designation, Serial diagnostic SD | OUT |
| Operation current | 100 mA |
| Design of control elements | short-circuit proof, p-type |
| Wiring capacitance | 50 nF |

Pin assignment

| | |
|-------|------------------------------|
| PIN 1 | A1 Supply voltage UB |
| PIN 2 | X1 Safety input 1 |
| PIN 3 | A2 GND |
| PIN 4 | Y1 Safety output 1 |
| PIN 5 | OUT serial diagnostic output |
| PIN 6 | X2 Safety input 2 |
| PIN 7 | Y2 Safety output 2 |
| PIN 8 | IN serial diagnostic input |


Pictures

Product picture (catalogue individual photo)



ID: kbdf2f03
 | 1.5 MB | .jpg | 352.778 x 802.217 mm - 1000 x 2274 px - 72 dpi
 | 26.1 kB | .png | 22.013 x 50.038 mm - 260 x 591 px - 300 dpi
 | 125.1 kB | .png | 74.083 x 168.275 mm - 210 x 477 px - 72 dpi
 | 49.5 kB | .jpg | 54.328 x 123.472 mm - 154 x 350 px - 72 dpi

Dimensional drawing basic component




ID: 1bdf2g03

| 358.0 kB | .cdr |

| 14.8 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi

| 164.7 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

Operating principle




ID: kbdf-a08

| 284.5 kB | .jpg | 352.778 x 281.517 mm - 1000 x 798 px - 72 dpi

| 5.0 kB | .png | 74.083 x 59.267 mm - 210 x 168 px - 72 dpi

Clipart




ID: kbdf-c03

| 64.1 kB | .cdr |

| 7.7 kB | .png | 74.083 x 404.989 mm - 210 x 1148 px - 72 dpi

Contact arrangement



ID: km23-k8a

| 18.0 kB | .cdr |

| 5.5 kB | .png | 73.731 x 79.728 mm - 209 x 226 px - 72 dpi

| 155.6 kB | .jpg | 352.778 x 380.647 mm - 1000 x 1079 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 21/08/2024, 5:50 am