



## SSB-R-NG-1-O-S-V01

- Magnetic track sensor box
- 4 tracks, 2 optional for fine positioning
- optional fine positioning tracks with prewarning indication
- Maintenance-free signal storage and switching in case of power failure
- Wide angle LED track display

## Data

### Ordering data

Product type description	SSB-R-NG-1-O-S-V01
Article number (order number)	103038393
EAN (European Article Number)	4030661566160
eCl@ss number, version 12.0	27-27-43-02
eCl@ss number, version 11.0	27-27-01-05
eCl@ss number, version 9.0	27-27-01-05
ETIM number, version 7.0	EC002544
ETIM number, version 6.0	EC002544

### Approvals - Standards

Certificates	cULus
--------------	-------

### General data

Working principle	Magnetic drive
Housing material	Plastic, glass-fibre-reinforced
Material of the housing cover	Polycarbonate

Gross weight	314 g
--------------	-------

### General data - Features

Latching	Yes
Suitable for elevators	Yes
Number of LEDs	5
Number of snap-in contacts	4
Number of signalling outputs	4

### Mechanical data

Actuating panels	front side
Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Minimum distance devices	50 mm
Actuation direction	On when driving over with north magnet in driving direction
Actuating speed, maximum	9 m/s
Mounting	rear with 2 threaded bolts
Type of the fixing screws	2x M4
Tightening torque of the fixing screws, minimum	2 Nm
Tightening torque of the fixing screws, maximum	4 Nm

### Mechanical data - Switching distances according EN IEC 60947-5-3

Switching distance $S_{min}$ , minimum	2 mm
Switching distance $S_{max}$ , maximum	15 mm
Note (switching distance)	Recommended 7mm
Repeat accuracy R	0.5 mm

### Mechanical data - Connection technique

Terminal (mechanical)	Connector plug M12, 8-pole, A-coded
-----------------------	-------------------------------------

## Mechanical data - connector side A

Connector typ	Male connector, M12
Connector coding	A
Connector latching	Screw locking
Number of pol, side A	8

## Mechanical data - Dimensions

Length of sensor	125 mm
Width of sensor	110 mm
Height of sensor	24.4 mm

## Ambient conditions

Degree of protection	IP54 IP65
Ambient temperature	-25 ... +70 °C
Storage and transport temperature	-40 ... +85 °C
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations	10 ... 55 Hz, amplitude 1 mm
Restistance to shock	30 g / 11 ms
Protection class	III
Permissible installation altitude above sea level, maximum	2,000 m

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	32 VDC
Rated impulse withstand voltage $U_{imp}$	1 kV
Overvoltage category	III
Degree of pollution	3
Degree of pollution	3

## Electrical data

Current consumption at 24V, minimum	11 mA
No-load supply current $I_0$ , typical	20 mA
Rated operating voltage	24 VDC
Operating current	1,500 mA
Utilisation category DC-12	24 VDC
Utilisation category DC-12	0.3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	0.3 A
Switching capacity, maximum	7.2 W
Switching element	bistable contact
Switching principle	Reed contacts, Non-contact principle
Bounce duration, maximum	0.3 ms
Maximum switching time close	1 ms
Maximum switching time open	0.1 ms

## Electrical data - Digital Output

Output current, maximum	300 mA
Design of control elements	Reed contacts

## Accessory

Recommendation (actuator)	BP 15 BP 15/2
Recommendation (actuator, lift switchgear)	BP 15

## Pictures

### Product picture (catalogue individual photo)




ID: kssbrf09

| 341.6 kB | .jpg | 352.778 x 299.861 mm - 1000 x 850 px - 72 dpi

| 30.4 kB | .png | 74.083 x 63.147 mm - 210 x 179 px - 72 dpi

| 51.3 kB | .jpg | 123.472 x 105.128 mm - 350 x 298 px - 72 dpi

## Dimensional drawing basic component



ID: mssbrg01

| 104.8 kB | .jpg | 352.778 x 199.319 mm - 1000 x 565 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 22/08/2024, 5:13 am