

Product datasheet

Specifications



Easy TeSys control relay - 4 NO <= 690 V - 220 VAC

CAE40M5

Main

Range	Easy TeSys
Range of product	Easy TeSys Control Relay
Product or component type	Control relay
Device short name	CAE
contactor application	Control circuit
Colour	Grey (RAL 7011)

Complementary

Utilisation category	AC-14 AC-15
Pole contact composition	4 NO
[Ue] rated operational voltage	<= 690 V AC
Control circuit type	AC at 50 Hz
[Uc] control circuit voltage	220 V AC 50 Hz
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
[Ith] conventional free air thermal current	10 A (at 40 °C)
Irms rated making capacity	140 A at 690 V AC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	120 A - 500 ms 140 A - 100 ms
Associated fuse rating	10 A gG at 690 V conforming to IEC 60947-5-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: solid without cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: solid without cable end
Recommended tightening torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2
Control circuit voltage limits	Operational: 0.85...1.1 U _c at 50 Hz Drop-out: 0.3...0.6 U _c
Operating time	12...22 ms coil energisation and NO closing 6...17 ms coil de-energisation and NO closing
Mechanical durability	10 Mcycles
Maximum operating rate	180 cyc/mn

Inrush power in VA	70 VA 50 Hz (at 20 °C)
Hold-in power consumption in VA	8 VA 50 Hz (at 20 °C)
Minimum switching voltage	17 V
Minimum switching current	5 mA
Insulation resistance	> 10 MOhm
Mechanical robustness	Shocks control relay open: 7 Gn for 11 ms Shocks control relay closed: 10 Gn for 11 ms Vibrations control relay open: 1.5 Gn, 5...300 Hz Vibrations control relay closed: 3 Gn, 5...300 Hz
Height	74 mm
Width	45 mm
Depth	80 mm
Net weight	0.28 kg

Environment

Standards	IEC 60947-5-1
product certifications	GOST
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	7.5 cm
Package 1 Length	8.7 cm
Package 1 Weight	291.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	36
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10080.32 g
Unit Type of Package 3	P06
Number of Units in Package 3	576
Package 3 Height	115.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	179.32 kg

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)

Offer Marketing Illustration

Product benefits / Features

Easy TeSys Control Relays



Designed for the essential

Delivers the best balance between performance and budget without any compromise on quality



Easy choice and application

Easier to install, order and understand, and operate with multi-standard screws



Cost-effective

Provides a cost-effective solution to simple light duty applications



Offer Marketing Illustration

Product benefits / Features



Easy TeSys
Control Relays
Range Accessories

Contactor Coil

Auxiliary contact block

Connection block

Terminal block

Suppressor module

The image displays a collection of accessories for Easy TeSys control relays. At the top left, a main relay unit is shown against a green circular background. Below it, five individual components are presented with their respective labels: a black contactor coil, a black auxiliary contact block, a grey connection block, a black terminal block, and a white suppressor module with gold pins.

Offer Marketing Illustration

Product benefits / Features

Easy TeSys Control Relays

Technical Benefits



- For demanding applications with standard operating rates until 3 cycles/second.
- Up to 10 million mechanical operation cycles
- Compact (45mm width), for clipping on 35mm DIN rail or fixing by screw.
- 3 combinations: 2NO/2NC, 3NO/1NC, 4NO
- Multi-standards certified (IEC, CCC, EAC) and Green Premium compliant (RoHs/Reach).

Technical Illustration

Assembly's dimensions

mm
[in]

