

Product datasheet

Specifications



Easy TeSys contactor 3P(3 NO) - AC-3 - ≤ 440 V 160A - 110 V AC coil

LC1E160F5

Main

Range	Easy TeSys
Range of product	Easy TeSys Control
Product or component type	Contactors
Device short name	LC1E
contactor application	Motor control Resistive load
Utilisation category	AC-3 AC-1
poles description	3P
[Ue] rated operational voltage	Power circuit: ≤ 690 V AC 50/60 Hz
[Ie] rated operational current	160 A (at ≤ 55 °C) at ≤ 440 V AC AC-3 for power circuit 200 A (at ≤ 55 °C) at ≤ 440 V AC AC-1 for power circuit
[Uc] control circuit voltage	110 V AC 50 Hz

Complementary

Motor power kW	45 kW at 220...230 V AC 50/60 Hz 75 kW at 380...400 V 80 kW at 415 V 80 kW at 440 V 90 kW at 500 V 100 kW at 660...690 V
Pole contact composition	3 NO
[Ith] conventional free air thermal current	200 A (at 40 °C)
Irms rated making capacity	1600 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	1280 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	1400 A 40 °C - 10 s for power circuit
Associated fuse rating	10 A gG at ≤ 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 315 A gG at ≤ 690 V coordination type 1 for power circuit
Average impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power dissipation per pole	24 W AC-1 15 W AC-3
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	8 kV coil not connected to the power circuit conforming to IEC 60947

Mechanical durability	4000000 cycles
Electrical durability	800000 cycles AC-3 250000 cycles AC-1
Control circuit type	AC at 50 Hz
Control circuit voltage limits	0.85...1.1 U _c (-5...55 °C):operational 50 Hz 0.35...0.55 U _c (-5...55 °C):drop-out 50 Hz
Inrush power in VA	300 VA 50 Hz cos phi 0.9 (at 20 °C) 300 VA 60 Hz cos phi 0.9 (at 20 °C)
Hold-in power consumption in VA	22 VA 50 Hz cos phi 0.9 (at 20 °C) 22 VA 60 Hz cos phi 0.9 (at 20 °C)
Heat dissipation	3...8 W for control circuit
Operating time	20...50 ms on closing 6...20 ms on opening
Maximum operating rate	1200 cyc/h 55 °C
Connections - terminals	Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 10...120 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 10...120 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...2.5 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 10...120 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 10...120 mm ² - cable stiffness: solid without cable end
Tightening torque	Power circuit: 12 N.m Control circuit: 1.2 N.m
Auxiliary contact composition	1 NO + 1 NC
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
mounting support	DIN rail Plate

Environment

Standards	IEC 60947-5-1 IEC 60947-1 IEC 60947-4-1
product certifications	EAC CE
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH (pollution degree 3) conforming to IEC 60068-2-30 test Db
Permissible ambient air temperature around the device	-20...70 °C at U _c -60...80 °C storage -5...55 °C operation
Operating altitude	3000 m without derating

Fire resistance	850 °C conforming to IEC 60695-2-1
Mechanical robustness	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms)
Height	158 mm
Width	120 mm
Depth	132 mm
Net weight	2.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.0 cm
Package 1 Width	16.6 cm
Package 1 Length	21.1 cm
Package 1 Weight	2.406 kg
Unit Type of Package 2	P06
Number of Units in Package 2	24
Package 2 Height	75.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	70.74 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)

Offer Marketing Illustration

Product benefits / Features



Easy TeSys Contactors
Range Accessories

Mechanical interlock

Auxiliary contact block

Time delay auxiliary contact block

Terminal block

Suppressor module

The image displays a collection of electrical accessories for Easy TeSys contactors. At the top left, a large contactor is shown against a green background. Below it, five different accessories are presented with their respective labels: a mechanical interlock (two black plastic pieces), an auxiliary contact block (two black modules), a time delay auxiliary contact block (a black module with a circular dial), a terminal block (a black plastic component with multiple terminals), and a suppressor module (a tan-colored component with two terminals).

Offer Marketing Illustration

Product benefits / Features

Easy TeSys Contactors

Technical Benefits



- 9 sizes cover common applications from 6 to 630A.
- Designed to meet the requirements of Electro-domestic and HVAC applications.
- Various Relay Coil Voltages: A.C.
- It can cover -5°C to 55°C working temperature and mounted by DIN-rail, No derating up to 3000m altitude.
- 2.2kW to 335kW (AC3/400V)
- Multi-standards certified (IEC, CCC, EAC) and Green Premium compliant (RoHs/Reach).

Offer Marketing Illustration

Product benefits / Features

Easy TeSys Contactors



Designed for the essential

Deliver the best balance between performance and budget without any compromise on quality



Easy to use

Easier to install and operate with multi-standard screws



Cost-effective

Provides a cost-effective solution to a simple application



Technical Illustration

Assembly's dimensions

