

# Product datasheet

Specifications



## Easy TeSys contactor 3P(3 NO) - AC-3 - $\leq 440$ V 65A - 24 V AC coil

LC1E65B7

### Main

Range	Easy TeSys
Range of product	Easy TeSys Control
Product or component type	Contactors
Device short name	LC1E
contactor application	Resistive load Motor control
Utilisation category	AC-1 AC-3
poles description	3P
[Ue] rated operational voltage	Power circuit: $\leq 690$ V AC 50/60 Hz
[Ie] rated operational current	65 A (at $\leq 55$ °C) at $\leq 440$ V AC AC-3 for power circuit 80 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-1 for power circuit
[Uc] control circuit voltage	24 V AC 50/60 Hz

### Complementary

Motor power kW	18.5 kW at 220...230 V AC 50/60 Hz 30 kW at 380...400 V 37 kW at 415 V 37 kW at 440 V 37 kW at 500 V 37 kW at 660...690 V
Pole contact composition	3 NO
[Ith] conventional free air thermal current	80 A (at 55 °C)
Irms rated making capacity	650 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	520 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	520 A 40 °C - 10 s for power circuit 260 A 40 °C - 60 s for power circuit 110 A 40 °C - 600 s for power circuit
Associated fuse rating	10 A gG at $\leq 690$ V coordination type 1 for control circuit conforming to IEC 60947-5-1 125 A gG at $\leq 690$ V coordination type 1 for power circuit
Average impedance	1 mOhm - Ith 80 A 50 Hz for power circuit
Power dissipation per pole	4.2 W AC-3 6.4 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3

<b>[Uimp] rated impulse withstand voltage</b>	6 kV coil not connected to the power circuit conforming to IEC 60947
<b>Mechanical durability</b>	5000000 cycles
<b>Electrical durability</b>	350000 cycles AC-1 900000 cycles AC-3
<b>Control circuit type</b>	AC at 50/60 Hz
<b>Control circuit voltage limits</b>	0.85...1.1 U <sub>c</sub> (-5...55 °C):operational 50/60 Hz 0.3...0.6 U <sub>c</sub> (-5...55 °C):drop-out 50/60 Hz
<b>Inrush power in VA</b>	160 VA 50 Hz cos phi 0.75 (at 20 °C) 140 VA 60 Hz cos phi 0.75 (at 20 °C)
<b>Hold-in power consumption in VA</b>	15 VA 50 Hz cos phi 0.3 (at 20 °C) 13 VA 60 Hz cos phi 0.3 (at 20 °C)
<b>Heat dissipation</b>	6...10 W for control circuit
<b>Operating time</b>	20...26 ms on closing 8...12 ms on opening
<b>Maximum operating rate</b>	1200 cyc/h 60 °C
<b>Connections - terminals</b>	Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 2.5...25 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 2.5...10 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 2.5...25 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 2.5...16 mm <sup>2</sup> - cable stiffness: solid without cable end
<b>Tightening torque</b>	Control circuit: 1.2 N.m Power circuit: 5 N.m
<b>Auxiliary contact composition</b>	1 NO + 1 NC
<b>Minimum switching voltage</b>	17 V for control circuit
<b>Minimum switching current</b>	5 mA for control circuit
<b>Insulation resistance</b>	> 10 MOhm for control circuit
<b>Non-overlap time</b>	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
<b>mounting support</b>	Plate DIN rail

## Environment

<b>Standards</b>	IEC 60947-1 IEC 60947-5-1 IEC 60947-4-1
<b>product certifications</b>	EAC CE
<b>IP degree of protection</b>	IP2X conforming to IEC 60529
<b>Protective treatment</b>	TH (pollution degree 3) conforming to IEC 60068-2-30 test Db

<b>Permissible ambient air temperature around the device</b>	-20...70 °C at Uc -60...80 °C storage -5...55 °C operation
<b>Operating altitude</b>	3000 m without derating
<b>Fire resistance</b>	850 °C conforming to IEC 60695-2-1
<b>Mechanical robustness</b>	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms)
<b>Height</b>	127 mm
<b>Width</b>	75 mm
<b>Depth</b>	114 mm
<b>Net weight</b>	0.98 kg

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	12.000 cm
<b>Package 1 Width</b>	8.000 cm
<b>Package 1 Length</b>	12.900 cm
<b>Package 1 Weight</b>	920.000 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	9
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	9.356 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

---

Toxic Heavy Metal Free

---

Mercury Free

---

Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

**Circularity Profile** [End of Life Information](#)

---

Offer Marketing Illustration

Product benefits / Features

---



Easy TeSys Contactors  
Range Accessories

Mechanical interlock

Auxiliary contact block

Time delay auxiliary contact block

Terminal block

Suppressor module

The image displays six different accessories for Easy TeSys contactors. At the top left is a large black contactor. Below it are: 1) Mechanical interlock (two black plastic pieces), 2) Auxiliary contact block (two black modules with orange handles), 3) Time delay auxiliary contact block (a black module with a circular dial), 4) Terminal block (a black plastic component with multiple terminals), and 5) Suppressor module (a tan-colored component with two terminals).

Offer Marketing Illustration

Product benefits / Features

---



**Easy TeSys Contactors**  
Technical Benefits

- 9 sizes cover common applications from 6 to 630A.
- Designed to meet the requirements of Electro-domestic and HVAC applications.
- Various Relay Coil Voltages: A.C.
- It can cover -5°C to 55°C working temperature and mounted by DIN-rail, No derating up to 3000m altitude.
- 2.2kW to 335kW (AC3/400V)
- Multi-standards certified (IEC, CCC, EAC) and Green Premium compliant (RoHs/Reach).

Offer Marketing Illustration

Product benefits / Features

---

## Easy TeSys Contactors

-  **Designed for the essential**  
Deliver the best balance between performance and budget without any compromise on quality
-  **Easy to use**  
Easier to install and operate with multi-standard screws
-  **Cost-effective**  
Provides a cost-effective solution to a simple application



Technical Illustration

Assembly's dimensions

---

