





# TeSys LRD thermal overload relays

LRD3312

### Main

Range	TeSys	
Product name	TeSys LRD	
	TeSys Deca	
Product or component type	Differential thermal overload relay	
Device short name	LRD	
Relay application	Motor protection	
Network type	DC	
Thermal overload class	Class 10A conforming to IEC 60947-4-1	
Thermal protection adjustment range	5.58 A	

### Complementary

Tripping threshold	1.14 +/- 0.06 Ir conforming to IEC 60947-4-1	
Auxiliary contact composition	1 NO + 1 NC	
[Ith] conventional free air thermal current	5 A for signalling circuit	
Permissible current	3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit	
[Ue] rated operational voltage	1000 V AC 0400 Hz for power circuit conforming to IEC 60947-4-1	
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit	
[Uimp] rated impulse withstand voltage	6 kV	
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0	
Control type	Red push-button: stop Blue push-button: reset	
Temperature compensation -2060 °C		
Height	81 mm	
Width	70 mm	
Depth	115 mm	
Net weight 0.51 kg		

### **Environment**

Climatic withstand	conforming to IACS E10	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	-2060 °C without derating conforming to IEC 60947-4-1	

Ambient air temperature for storage	-6070 °C		
Dielectric strength	2.2 kV at 50 Hz conforming to IEC 60947-1		
Standards	EN/IEC 60947-4-1		
	EN/IEC 60947-5-1		
	UL 60947-4-1		
	UL 60947-5-1		
	CSA C22.2 No 60947-4-1		
	CSA C22.2 No 60947-5-1		
	GB/T 14048.4		
	GB/T 14048.5		
product certifications	IEC		
	UL		
	CSA		
	CCC		
	EAC		
	UKCA		
	CE		

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	12.0 cm
Package 1 Length	8.5 cm
Package 1 Weight	500.0 g

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information