Product datasheet

Specifications

Green Premium™

remote terminal, Altivar, for variable speed drive, IP54

VW3A1006

Main

Range of product	Altivar
accessory / separate part type	Remote terminal
accessory / separate part category	Display and signalling accessory
accessory / separate part destination	Variable speed drive
Range compatibility	Altivar Machine ATV320 Altivar 32 Altivar 12 Easy Altivar 310 Altivar 312 Solar Altivar 312
IP degree of protection	IP54

Complementary

mounting location	Door of enclosure
Net weight	0.25 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	66.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	90
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.725 kg

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation   China RoHS declaration

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations

Dimensions Drawings

Dimensions

mm
in.

15 / 0.59

70 / 2.76

7.7 / 0.30

50 / 1.97

34 / 1.34

17.5 / 0.69

Ø 28 / Ø 1.10

29.2 / 1.15

54 / 2.13

2.3 / 0.09

29.4 / 1.16

4 x Ø 3.5 / 4 x Ø 0.14