



power contactor, AC-3e/AC-3 500 A, 250 kW / 400 V AC (50-60 Hz) / DC U_c: 96-127 V PLC input 24 V DC 3-pole, auxiliary contacts 2 NO + 2 NC drive: electronic main circuit: busbar control and auxiliary circuit: screw terminal

| | |
|--|----------------------------|
| product brand name | SIRIUS |
| product designation | Power contactor |
| product type designation | 3RT1 |
| General technical data | |
| size of contactor | S12 |
| product extension | |
| • function module for communication | No |
| • auxiliary switch | Yes |
| power loss [W] for rated value of the current | |
| • at AC in hot operating state | 165 W |
| • at AC in hot operating state per pole | 55 W |
| • without load current share typical | 3.6 W |
| type of calculation of power loss depending on pole | quadratic |
| insulation voltage | |
| • of main circuit with degree of pollution 3 rated value | 1 000 V |
| • of auxiliary circuit with degree of pollution 3 rated value | 500 V |
| surge voltage resistance | |
| • of main circuit rated value | 8 kV |
| • of auxiliary circuit rated value | 6 kV |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 690 V |
| shock resistance at rectangular impulse | |
| • at AC | 8,5g / 5 ms, 4,2g / 10 ms |
| • at DC | 8,5g / 5 ms, 4,2g / 10 ms |
| shock resistance with sine pulse | |
| • at AC | 13,4g / 5 ms, 6,5g / 10 ms |
| • at DC | 13,4g / 5 ms, 6,5g / 10 ms |
| mechanical service life (operating cycles) | |
| • of contactor typical | 10 000 000 |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000 |
| • of the contactor with added auxiliary switch block typical | 10 000 000 |
| reference code according to IEC 81346-2 | Q |
| Substance Prohibitance (Date) | |
| SVHC substance name | Lead - 7439-92-1 |
| Weight | 10.51 kg |
| Ambient conditions | |
| installation altitude at height above sea level maximum | 2 000 m |
| ambient temperature | |
| • during operation | -25 ... +60 °C |
| • during storage | -55 ... +80 °C |

| | |
|--|---------------------|
| relative humidity minimum | 10 % |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum | 95 % |
| Main circuit | |
| number of poles for main current circuit | 3 |
| number of NO contacts for main contacts | 3 |
| operating voltage | |
| • at AC-3 rated value maximum | 1 000 V |
| • at AC-3e rated value maximum | 1 000 V |
| operational current | |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value | 610 A |
| • at AC-1 | |
| — up to 690 V at ambient temperature 40 °C rated value | 610 A |
| — up to 690 V at ambient temperature 60 °C rated value | 550 A |
| — up to 1000 V at ambient temperature 40 °C rated value | 200 A |
| — up to 1000 V at ambient temperature 60 °C rated value | 200 A |
| • at AC-3 | |
| — at 400 V rated value | 500 A |
| — at 500 V rated value | 500 A |
| — at 690 V rated value | 450 A |
| — at 1000 V rated value | 180 A |
| • at AC-3e | |
| — at 400 V rated value | 500 A |
| — at 500 V rated value | 500 A |
| — at 690 V rated value | 450 A |
| — at 1000 V rated value | 180 A |
| • at AC-4 at 400 V rated value | 430 A |
| • at AC-5a up to 690 V rated value | 536 A |
| • at AC-5b up to 400 V rated value | 415 A |
| • at AC-6a | |
| — up to 230 V for current peak value n=20 rated value | 414 A |
| — up to 400 V for current peak value n=20 rated value | 414 A |
| — up to 500 V for current peak value n=20 rated value | 414 A |
| — up to 690 V for current peak value n=20 rated value | 414 A |
| — up to 1000 V for current peak value n=20 rated value | 180 A |
| • at AC-6a | |
| — up to 230 V for current peak value n=30 rated value | 276 A |
| — up to 400 V for current peak value n=30 rated value | 276 A |
| — up to 500 V for current peak value n=30 rated value | 276 A |
| — up to 690 V for current peak value n=30 rated value | 276 A |
| — up to 1000 V for current peak value n=30 rated value | 180 A |
| minimum cross-section in main circuit at maximum AC-1 rated value | 370 mm ² |
| operational current for approx. 200000 operating cycles at AC-4 | |
| • at 400 V rated value | 175 A |
| • at 690 V rated value | 150 A |
| operational current | |
| • at 1 current path at DC-1 | |
| — at 24 V rated value | 400 A |
| — at 60 V rated value | 330 A |
| — at 110 V rated value | 33 A |
| — at 220 V rated value | 3.8 A |
| — at 440 V rated value | 0.9 A |
| — at 600 V rated value | 0.6 A |
| • with 2 current paths in series at DC-1 | |
| — at 24 V rated value | 400 A |

| | |
|--|-------------|
| — at 60 V rated value | 400 A |
| — at 110 V rated value | 400 A |
| — at 220 V rated value | 400 A |
| — at 440 V rated value | 4 A |
| — at 600 V rated value | 2 A |
| ● with 3 current paths in series at DC-1 | |
| — at 24 V rated value | 400 A |
| — at 60 V rated value | 400 A |
| — at 110 V rated value | 400 A |
| — at 220 V rated value | 400 A |
| — at 440 V rated value | 11 A |
| — at 600 V rated value | 5.2 A |
| ● at 1 current path at DC-3 at DC-5 | |
| — at 24 V rated value | 400 A |
| — at 60 V rated value | 11 A |
| — at 220 V rated value | 0.6 A |
| — at 440 V rated value | 0.18 A |
| — at 600 V rated value | 0.125 A |
| ● with 2 current paths in series at DC-3 at DC-5 | |
| — at 24 V rated value | 400 A |
| — at 60 V rated value | 400 A |
| — at 110 V rated value | 400 A |
| — at 220 V rated value | 2.5 A |
| — at 440 V rated value | 0.65 A |
| — at 600 V rated value | 0.37 A |
| ● with 3 current paths in series at DC-3 at DC-5 | |
| — at 24 V rated value | 400 A |
| — at 60 V rated value | 400 A |
| — at 110 V rated value | 400 A |
| — at 220 V rated value | 400 A |
| — at 440 V rated value | 1.4 A |
| — at 600 V rated value | 0.75 A |
| operating power | |
| ● at AC-3 | |
| — at 230 V rated value | 160 kW |
| — at 400 V rated value | 250 kW |
| — at 500 V rated value | 315 kW |
| — at 690 V rated value | 400 kW |
| — at 1000 V rated value | 250 kW |
| ● at AC-3e | |
| — at 230 V rated value | 160 kW |
| — at 400 V rated value | 250 kW |
| — at 500 V rated value | 315 kW |
| — at 690 V rated value | 400 kW |
| — at 1000 V rated value | 250 kW |
| operating power for approx. 200000 operating cycles at AC-4 | |
| ● at 400 V rated value | 98 kW |
| ● at 690 V rated value | 148 kW |
| operating apparent power at AC-6a | |
| ● up to 230 V for current peak value n=20 rated value | 160 000 kVA |
| ● up to 400 V for current peak value n=20 rated value | 280 000 VA |
| ● up to 500 V for current peak value n=20 rated value | 350 000 VA |
| ● up to 690 V for current peak value n=20 rated value | 490 000 VA |
| ● up to 1000 V for current peak value n=20 rated value | 310 000 VA |
| operating apparent power at AC-6a | |
| ● up to 230 V for current peak value n=30 rated value | 110 000 VA |
| ● up to 400 V for current peak value n=30 rated value | 190 000 VA |
| ● up to 500 V for current peak value n=30 rated value | 230 000 VA |
| ● up to 690 V for current peak value n=30 rated value | 330 000 VA |
| ● up to 1000 V for current peak value n=30 rated value | 310 000 VA |

| | |
|---|--|
| short-time withstand current in cold operating state up to 40 °C | |
| <ul style="list-style-type: none"> ● limited to 1 s switching at zero current maximum ● limited to 5 s switching at zero current maximum ● limited to 10 s switching at zero current maximum ● limited to 30 s switching at zero current maximum ● limited to 60 s switching at zero current maximum | <p>7 484 A; Use minimum cross-section acc. to AC-1 rated value</p> <p>7 484 A; Use minimum cross-section acc. to AC-1 rated value</p> <p>5 978 A; Use minimum cross-section acc. to AC-1 rated value</p> <p>3 765 A; Use minimum cross-section acc. to AC-1 rated value</p> <p>2 887 A; Use minimum cross-section acc. to AC-1 rated value</p> |
| no-load switching frequency | |
| <ul style="list-style-type: none"> ● at AC ● at DC | <p>1 000 1/h</p> <p>1 000 1/h</p> |
| operating frequency | |
| <ul style="list-style-type: none"> ● at AC-1 maximum ● at AC-2 maximum ● at AC-3 maximum ● at AC-3e maximum ● at AC-4 maximum | <p>500 1/h</p> <p>170 1/h</p> <p>420 1/h</p> <p>420 1/h</p> <p>130 1/h</p> |
| Control circuit/ Control | |
| type of voltage of the control supply voltage | AC/DC |
| control supply voltage at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz rated value ● at 60 Hz rated value | <p>96 ... 127 V</p> <p>96 ... 127 V</p> |
| control supply voltage at DC rated value | 96 ... 127 V |
| operating range factor control supply voltage rated value of magnet coil at DC | |
| <ul style="list-style-type: none"> ● initial value ● full-scale value | <p>0.8</p> <p>1.1</p> |
| operating range factor control supply voltage rated value of magnet coil at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz | <p>0.8 ... 1.1</p> <p>0.8 ... 1.1</p> |
| type of PLC-control input according to IEC 60947-1 | Type 2 |
| consumed current at PLC-control input according to IEC 60947-1 maximum | 20 mA |
| voltage at PLC-control input rated value | 24 V |
| operating range factor of the voltage at PLC-control input | 0.8 ... 1.1 |
| design of the surge suppressor | with varistor |
| apparent pick-up power | |
| <ul style="list-style-type: none"> ● at minimum rated control supply voltage at AC <ul style="list-style-type: none"> — at 50 Hz — at 60 Hz ● at maximum rated control supply voltage at AC <ul style="list-style-type: none"> — at 60 Hz — at 50 Hz | <p>560 VA</p> <p>560 VA</p> <p>750 VA</p> <p>750 VA</p> |
| apparent pick-up power of magnet coil at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz | <p>750 VA</p> <p>750 VA</p> |
| inductive power factor with closing power of the coil | |
| <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz | <p>0.8</p> <p>0.8</p> |
| apparent holding power | |
| <ul style="list-style-type: none"> ● at minimum rated control supply voltage at DC ● at maximum rated control supply voltage at DC | <p>3 VA</p> <p>3.6 VA</p> |
| apparent holding power | |
| <ul style="list-style-type: none"> ● at minimum rated control supply voltage at AC <ul style="list-style-type: none"> — at 50 Hz — at 60 Hz ● at maximum rated control supply voltage at AC <ul style="list-style-type: none"> — at 50 Hz — at 60 Hz | <p>5.6 VA</p> <p>5.6 VA</p> <p>9 VA</p> <p>9 VA</p> |
| inductive power factor with the holding power of the coil | |
| <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz | <p>0.5</p> <p>0.4</p> |

| | |
|--|--|
| closing power of magnet coil at DC | 800 W |
| holding power of magnet coil at DC | 3.6 W |
| closing delay | |
| • at AC | 60 ... 90 ms |
| • at DC | 60 ... 90 ms |
| opening delay | |
| • at AC | 80 ... 100 ms |
| • at DC | 80 ... 100 ms |
| arcing time | 10 ... 15 ms |
| control version of the switch operating mechanism | PLC-IN or Standard A1 - A2 (adjustable) |
| Auxiliary circuit | |
| number of NC contacts for auxiliary contacts instantaneous contact | 2 |
| number of NO contacts for auxiliary contacts instantaneous contact | 2 |
| operational current at AC-12 maximum | 10 A |
| operational current at AC-15 | |
| • at 230 V rated value | 6 A |
| • at 400 V rated value | 3 A |
| • at 500 V rated value | 2 A |
| • at 690 V rated value | 1 A |
| operational current at DC-12 | |
| • at 24 V rated value | 10 A |
| • at 48 V rated value | 6 A |
| • at 60 V rated value | 6 A |
| • at 110 V rated value | 3 A |
| • at 125 V rated value | 2 A |
| • at 220 V rated value | 1 A |
| • at 600 V rated value | 0.15 A |
| operational current at DC-13 | |
| • at 24 V rated value | 10 A |
| • at 48 V rated value | 2 A |
| • at 60 V rated value | 2 A |
| • at 110 V rated value | 1 A |
| • at 125 V rated value | 0.9 A |
| • at 220 V rated value | 0.3 A |
| • at 600 V rated value | 0.1 A |
| contact reliability of auxiliary contacts | 1 faulty switching per 100 million (17 V, 1 mA) |
| UL/CSA ratings | |
| full-load current (FLA) for 3-phase AC motor | |
| • at 480 V rated value | 477 A |
| • at 600 V rated value | 472 A |
| yielded mechanical performance [hp] | |
| • for 3-phase AC motor | |
| — at 200/208 V rated value | 150 hp |
| — at 220/230 V rated value | 200 hp |
| — at 460/480 V rated value | 400 hp |
| — at 575/600 V rated value | 500 hp |
| contact rating of auxiliary contacts according to UL | A600 / Q600 |
| Short-circuit protection | |
| design of the fuse link | |
| • for short-circuit protection of the main circuit | |
| — with type of coordination 1 required | gG: 630 A (690 V, 100 kA) |
| — with type of assignment 2 required | gG: 500 A (690 V, 100 kA), aM: 500 A (690 V, 50 kA), BS88: 500 A (415 V, 50 kA) |
| • for short-circuit protection of the auxiliary switch required | gG: 10 A (500 V, 1 kA) |
| Installation/ mounting/ dimensions | |
| mounting position | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| fastening method | screw fixing |
| height | 214 mm |
| width | 160 mm |

| | |
|--|---|
| depth | 225 mm |
| required spacing | |
| <ul style="list-style-type: none"> ● with side-by-side mounting <ul style="list-style-type: none"> — forwards 20 mm — upwards 10 mm — downwards 10 mm — at the side 0 mm ● for grounded parts <ul style="list-style-type: none"> — forwards 20 mm — upwards 10 mm — at the side 10 mm — downwards 10 mm ● for live parts <ul style="list-style-type: none"> — forwards 20 mm — upwards 10 mm — downwards 10 mm — at the side 10 mm | |
| Connections/ Terminals | |
| type of electrical connection | |
| <ul style="list-style-type: none"> ● for main current circuit Connection bar ● for auxiliary and control circuit screw-type terminals ● at contactor for auxiliary contacts Screw-type terminals ● of magnet coil Screw-type terminals | |
| width of connection bar | 25 mm |
| thickness of connection bar | 6 mm |
| diameter of holes | 11 mm |
| number of holes | 1 |
| type of connectable conductor cross-sections | |
| <ul style="list-style-type: none"> ● for AWG cables for main contacts 2/0 ... 500 kcmil | |
| connectable conductor cross-section for main contacts | |
| <ul style="list-style-type: none"> ● stranded 70 ... 240 mm² | |
| connectable conductor cross-section for auxiliary contacts | |
| <ul style="list-style-type: none"> ● solid or stranded 0.5 ... 4 mm² ● finely stranded with core end processing 0.5 ... 2.5 mm² | |
| type of connectable conductor cross-sections | |
| <ul style="list-style-type: none"> ● for auxiliary contacts <ul style="list-style-type: none"> — solid 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), max. 2x (0.75 ... 4 mm²) — solid or stranded 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), max. 2x (0.75 ... 4 mm²) — finely stranded with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) ● for AWG cables for auxiliary contacts 2x (20 ... 16), 2x (18 ... 14), 1x 12 | |
| AWG number as coded connectable conductor cross section | |
| <ul style="list-style-type: none"> ● for auxiliary contacts 18 ... 14 | |
| Safety related data | |
| product function | |
| <ul style="list-style-type: none"> ● mirror contact according to IEC 60947-4-1 Yes ● positively driven operation according to IEC 60947-5-1 No ● suitable for safety function Yes | |
| suitability for use safety-related switching OFF | Yes; safety-related disconnection via A1 A2 |
| service life maximum | 20 a |
| test wear-related service life necessary | Yes |
| proportion of dangerous failures | |
| <ul style="list-style-type: none"> ● with low demand rate according to SN 31920 40 % ● with high demand rate according to SN 31920 73 % | |
| B10 value with high demand rate according to SN 31920 | 1 000 000 |
| failure rate [FIT] with low demand rate according to SN 31920 | 100 FIT |
| ISO 13849 | |
| device type according to ISO 13849-1 | 3 |
| overdimensioning according to ISO 13849-2 necessary | Yes |
| IEC 61508 | |

| | |
|---|--|
| safety device type according to IEC 61508-2 | Type A |
| Electrical Safety | |
| protection class IP on the front according to IEC 60529 | IP00; IP20 with box terminal/cover |
| touch protection on the front according to IEC 60529 | finger-safe, for vertical contact from the front with box terminal/cover |
| Approvals Certificates | |
| General Product Approval | |



[Confirmation](#)







| | | | |
|-----|--|--|--|
| EMV | Functional Safety | Test Certificates | Marine / Shipping |
| | Type Examination Certificate | Special Test Certificate | Type Test Certificates/Test Report |
| RCM | | | |

| | | | | | |
|-------------------|-------|------|-------------------------------|------------------------------|-------------------------------|
| Marine / Shipping | other | | | | |
| | | | Miscellaneous | Confirmation | Miscellaneous |
| LRS | PRS | RMRS | | | |

| | | |
|------------------------------|--|---|
| other | Railway | Environment |
| Confirmation | Special Test Certificate | Environmental Confirmations |

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1076-6NF36>
- Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1076-6NF36>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RT1076-6NF36>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1076-6NF36&lang=en
- Characteristic: Tripping characteristics, I²t, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RT1076-6NF36/char>
- Further characteristics (e.g. electrical endurance, switching frequency)
<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT1076-6NF36&objecttype=14&gridview=view1>



last modified:



