EOS2 1055 A

Order Code: 1320406

Body Detection Safety Light Curtain with Automatic Restart



Safety level

Type 2 - PL c

Protected height (mm)

1060

Resolution (mm)

50

Max. range (m)

12

Restart

Automatic

Functioning system

Emitter / Receiver

Technical Description

Compact Safety Light Curtain: Type 2, SIL 1, SILCL 1, PL c, Cat. 2

Cross Section: 28 x 30 mm No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

EOS2 1055 A



Features

Safety level	Type 2 - PL c
Protected height (mm)	1060
Resolution (mm)	50
Controlled height (mm)	1050
Max. range (m)	12
Restart	Automatic
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 2 - SIL 1 - SILCL 1 - PL c - Cat. 2
Operating temperature (°C)	- 30 55
Response time (ms)	9
Number of beams	28
Max. length of the connection	100 (50 between Master and Slave)
cables (m)	
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against
	short circuit, overload and reverse polarity
Connections	M12 5-pole connectors
MTTFD (ISO13849) years	270,2
PFHD (IEC 61508)	3,92E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Detection	Body
Protective enclosures	None



Packaging dimensions HxLxW 145 x 1170 x 200

(mm)

Product class C

Custom tariff 85365019

Electrical data


Power supply (VDC) $24 \pm 20\%$


Mechanical data


Overall height (mm)	1113
Cross section dimensions (mm)	28 x 30
Degree of protection	IP65 - IP67
Fastening	Back slot with set of LE type brackets (included) or to the top
	and lower end with swivel brackets SFB E (optional)
Gross weight (g)	3600,26



Technical drawings









Certificates















