EOS2 1504 X

Order Code: 1320319

Hand Detection Safety Light Curtain with Automatic/Manual Restart and EDM



Safety level

Type 2 - PL c

Protected height (mm)

1510

Resolution (mm)

40

Max. range (m)

12

Restart

Built-in - User selectable automatic or manual

Functioning system

Emitter / Receiver

Technical Description

Compact Safety Light Curtain: Type 2, SIL 1, SILCL 1, PL c, Cat. 2

Cross Section: 28 x 30 mm No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

EOS2 1504 X



Features

Safety level	Type 2 - PL c
Protected height (mm)	1510
Resolution (mm)	40
Controlled height (mm)	1500
Max. range (m)	12
Restart	Built-in - User selectable automatic or manual
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 2 - SIL 1 - SILCL 1 - PL c - Cat. 2
Operating temperature (°C)	- 30 55
Response time (ms)	14
Number of beams	51
Max. length of the connection	100 (50 between Master and Slave)
cables (m)	
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against
	short circuit, overload and reverse polarity
Connections	M12 5-pole connector (emitter), M12 8-pole connector
	(receiver)
MTTFD (ISO13849) years	182,2
PFHD (IEC 61508)	5,96E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	Integrated
Detection	Hand



Protective enclosures None

Packaging dimensions HxLxW 145 x 1620 x 200

(mm)

Product class C

Custom tariff 85365019

Electrical data

Power supply (VDC) 24 ± 20%

Mechanical data

Overall height (mm) 1563

Cross section dimensions (mm) 28 x 30

Degree of protection IP65 - IP67


Fastening Back slot with set of LE type brackets (included) or to the top


and lower end with swivel brackets SFB E (optional)


Gross weight (g) 4757,76



Technical drawings









Certificates















