

## **EOS2 453 AT**

Order Code: 1321223

Hand Detection Safety Light Curtain with Automatic Restart. Resistant to High Vibrations



**Safety level**

Type 2 - PL c

**Protected height (mm)**

460

**Resolution (mm)**

30

**Max. range (m)**

12

**Restart**

Automatic

**Functioning system**

Emitter / Receiver

## **Technical Description**

Compact Safety Light Curtain: Type 2, SIL 1, SILCL 1, PL c, Cat. 2

Cross Section: 28 x 30 mm

No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

## Features

Safety level	Type 2 - PL c
Protected height (mm)	460
Resolution (mm)	30
Controlled height (mm)	450
Max. range (m)	12
Restart	Automatic
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 2 - SIL 1 - SILCL 1 - PL c - Cat. 2
Operating temperature (°C)	- 30 ... 55
Response time (ms)	8
Number of beams	23
Max. length of the connection cables (m)	100
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and reverse polarity
Connections	M12 5-pole connectors
MTTFD (ISO13849) years	315,6
PFHD (IEC 61508)	3,31E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Special versions	High vibrations
Detection	Hand

## EOS2 453 AT

Operating Range (m)	12
Protective enclosures	None
Packaging dimensions HxLxW (mm)	145 x 540 x 200
Product class	C
Custom tariff	85365019

## Electrical data

Power supply (VDC)	24 ± 20%
--------------------	----------

## Mechanical data

Overall height (mm)	513
Cross section dimensions (mm)	28 x 30
Degree of protection	IP65 - IP67
Fastening	Back slot with set of LE type brackets (included) or to the top and lower end with swivel brackets SFB E (optional)

Technical drawings



**Certificates**

