

Finger Detection Safety Light Curtain with Automatic/Manual Restart and EDM. Resistant to High Vibrations



Safety level Type 4 - PL e

Protected height (mm) 610

Resolution (mm) 14

Max. range (m) 6

Restart

Built-in - User selectable automatic or manual

Functioning system Emitter / Receiver

Technical Description

Compact Safety Light Curtain: Type 4, SIL 3, SILCL 3, PL e, Cat. 4 Cross Section: 28 x 30 mm No blind area on one side Hardware configuration: no programming necessary, easy to install and replace Connection and configuration through M12 connectors Unshielded cables up to 100 m can be used to connect the Safety Light Curtain What's in the Box: Emitter, Receiver and Standard Fastening Brackets

EOS4 601 XT

Pag. 1/5

EXAMPLE R Your future's safe!

Features

Safety level	Type 4 - PL e
Protected height (mm)	610
Resolution (mm)	14
Controlled height (mm)	600
Max. range (m)	6
Restart	Built-in - User selectable automatic or manual
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
Operating temperature (°C)	- 30 55
Response time (ms)	9
Number of beams	60
Max. length of the connection	100
cables (m)	
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against
	short circuit, overload and reverse polarity
Connections	M12 5-pole connector (emitter), M12 8-pole connector
	(receiver)
MTTFD (ISO13849) years	395,8
PFHD (IEC 61508)	1,51E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Special versions	High vibrations
EOS4 601 XT	

Pag. 2/5

EXAMPLE R Your future's safe!

Detection	Finger
Operating Range (m)	6
Protective enclosures	None
Packaging dimensions HxLxW	0 x 0 x 0
(mm)	
Product class	C
Custom tariff	85365019

Electrical data


Power supply (VDC)	24 ± 20%
--------------------	----------

Mechanical data

Overall height (mm)	663
Cross section dimensions (mm)	28 x 30
Degree of protection	IP65 - IP67
Fastening	Back slot with set of LE type brackets (included) or to the top
	and lower end with swivel brackets SFB E (optional)



Technical drawings




EOS4 601 XT

Pag. 4/5



Certificates





EOS4 601 XT

