

## AD SRE3C

Order Code: 1330912

Safety Interface for E-Stops and Safety Switches, Manual Monitored Restart, Cat. 3 (2 NO contacts)



Safety level

PL d

Safety relay outputs

2 NO (6A at 250 VAC)

## Technical Description

Safety relay for emergency stop buttons and safety switches monitoring

- Guided-contact safety relays
- EDM Feedback input for external contactors monitoring
- Manual monitored Start/Restart
- Can be used up to safety Category 3, PL d according to EN ISO 13849-1

## Features

Safety level	PL d
Safety level (SIL / PL)	PL d - Cat. 3
Operating temperature (°C)	- 25 ... 55
Response time (ms)	
Signalling	LEDs indication for status and diagnostic: power supply, channel 1 and channel 2
Connections	Terminal blocks
MTTFD (ISO13849) years	100
Safety devices to be connected	Emergency stop buttons and safety switches
Start/Restart	Manual
Min. switching current at 24 VDC (mA)	6
Safety relay outputs	2 NO (6A at 250 VAC)
Packaging dimensions HxLxW (mm)	47 x 166 x 111
Product class	C
Custom tariff	85365080

## Electrical data

Power supply (VDC)	24 ± 20%
--------------------	----------

## Mechanical data

Dimensions HxWxD (mm)	99 x 22,5 x 114
-----------------------	-----------------

## AD SRE3C

Fastening 35 mm DIN rail fastening according to EN 50022-35 standard

Gross weight (g) 200

## Certificates

